

**[CLAIMS]**

[Claim 1] A drying rack in a dryer comprising:

a rack detachably mounted to an inside of a drying drum

5 for placing a drying object thereon; and

at least one drying stick for supporting the drying  
object spaced a predetermined distance from the rack.

[Claim 2] The drying rack as claimed in claim 1,

10 wherein the rack includes;

a seat having a plurality of pass through holes for  
pass through of drying air; and

a securing portion for supporting the seat spaced from  
a predetermined distance from an inside circumferential  
15 surface of the drying drum.

[Claim 3] The drying rack as claimed in claim 1,

wherein the drying stick is detachable from the rack.

20 [Claim 4] The drying rack as claimed in claim 1,

wherein the drying stick is formed to be extended upward  
from the rack.

[Claim 5] The drying rack as claimed in claim 1,

25 further comprising a seating plate at an end of the drying  
stick for seating the drying object thereon.

[Claim 6] The drying rack as claimed in claim 5,  
further comprising a branch stick having one end fixedly  
secured to a side of the drying stick, and the other end  
5 supporting the seating plate.

[Claim 7] The drying rack as claimed in claim 6,  
wherein the branch stick is formed as one body with the  
drying stick.

10

[Claim 8] The drying rack as claimed in claim 6,  
wherein the end of the drying stick and the end of the  
branch stick are at the same height.

15

[Claim 9] The drying rack as claimed in claim 1,  
wherein the drying stick has an upper end bent in a "L"  
shape.

[Claim 10] The drying rack as claimed in claim 9,  
20 wherein the bent portion of the drying stick has a flat  
upper surface.

[Claim 11] A drying rack in a dryer comprising:  
a seat having a plurality of pass through holes for  
25 pass through of drying air;  
a securing portion for supporting the seat spaced from

a predetermined distance from an inside circumferential surface of the drying drum; and

a drying stick at the seat for drying the drying object in a space spaced a distance from the seat.

5

[Claim 12] The drying rack as claimed in claim 11, wherein the drying stick is detachably mounted projected upward from the seat.

10 [Claim 13] The drying rack as claimed in claim 11, further comprising a branch stick at one side of the drying stick, the branch stick being branched in a direction different from the drying stick.

15 [Claim 14] The drying rack as claimed in claim 13, wherein both the drying stick and the branch stick have ends at the same height.

20 [Claim 15] The drying rack as claimed in claim 11, further comprising a seating plate at the end of the drying stick for seating the drying object.

25 [Claim 16] The drying rack as claimed in claim 11, wherein the drying stick has an upper end bent in a "n" shape.

[Claim 17] The drying rack as claimed in claim 16,  
wherein the bent portion of the drying stick has a flat  
upper surface.